



RenoSys Corporation

SoftSide™ Safety Padding System

Product Data, Features and Application Information:

Softside is an incredibly durable, ½" to 6" thick, slip resistant covered foam padding system designed for water playground and pool use. SoftSide consists of a thick foam pad system bonded to a textured, 100% virgin PVC cover skin. The SoftSide product is manufactured for today's demanding safety fall zone applications. Designers and end users can take comfort in knowing that the SoftSide Safety Padding System employs as our installation concept, the proven details and attributes developed for use with the RenoSys PVC Pool Shell. SoftSide may be purchased in floor area installations or as custom built watertight pads for owner installation. SoftSide is a member of the RenoSys family of commercial pool products which includes the: RenoSys PVC Pool Shell, RecDeck PVC Leisure Flooring, ToughDeck PVC Flooring, DuraTech Pool Gutters and Grating.

SoftSide Features:

- **Durable** Covered with a thick skin of tough PVC. SoftSide is warranted for 2 years.
- **Watertight** Totally watertight safety padding for underwater or pool deck applications.
- **Slip Resistant** The SoftSide surface skin material is highly slip resistant, even when wet. Perfect for wading pools.
- **Colorfast** As the outer skin wears, it maintains it's attractive color.
- **Versatile** SoftSide can be placed in fall zones or wherever extra safety and comfort is desired.
- **UV Stabilized** Maximum UV inhibitors are incorporated at the time of manufacture.
- **Algae and Fungus Resistant** Biocides are formulated into the foam and PVC material.
- **Low Maintenance** SoftSide can be mopped, pressure washed or sponge cleaned.
- **Resilient** Passes all CPSC-ASTM 1292 tests for impact attenuation to drop heights of 10'-0" (3" thick).
- **Hygienic** Because SoftSide doesn't allow liquids or solid material to penetrate, the padding can be maintained in a hygienic manner through topical applications of biocides, or proper pool chemistry.

SoftSide Applications:

- **Playground Areas 1" to 4"**
- **Pool Decks 2" to 6"**
- **Wading Pool Flooring ¼" to 2"**
- **Play Pool Safety Padding ¼" to 4"**
- **Aerobic Flooring ½"**
- **Locker Room Flooring ½"**
- **Under Diving Boards or Dive Stands 3" to 6"**
- **Water Slide Pads**
- **Wherever comfortable watertight safety padding is required.**

Technical Data:

Overall Thickness	¾" to 6 ½"
Outer Skin Thickness	60 mil adhered to foam
Roll Size	Varies Depends on thickness
Seams	Butt or lap welded or adhered
Method of Installation	Adhered and/or Bolt-down
Surface Texture	Slip resistant to smooth
Warranty	2 years
Colors	White, Lt. Blue, or Dk. Blue
Delivery	1 - 4 weeks

Ordering Information: When ordering or requesting a quotation on the SoftSide Safety Padding System, simply call us at our (800) number below. Have available the area to cover in square footage, the potential fall height of the user, and the substrate to pads will be installed on, as well as application information. We will review your requirements, provide pricing, and make installation recommendations. A written proposal, installation shop drawings, samples and details will then be provided for your approval. Installation of smaller pads can be performed by the customer.

